

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/111463 A1

(51) International Patent Classification⁷: **F04D 29/22**,
29/24, 7/04

[AU/AU]; 61 Nelson Street, Bedforddale, Western Australia
6112 (AU).

(21) International Application Number:
PCT/AU2004/000784

(74) Agents: **SMEETON, Anthony, Richard** et al.; Davies
Collison Cave, Level 10, 10 Barrack Street, Sydney, New
South Wales 2000 (AU).

(22) International Filing Date: 15 June 2004 (15.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003903024 16 June 2003 (16.06.2003) AU

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(71) Applicant (*for all designated States except US*): **WEIR
WARMAN LTD** [AU/AU]; 1 Marden Street, Artarmon,
New South Wales 2064 (AU).


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **WALKER, Craig,
Ian** [AU/AU]; 18A Gladys Avenue, Frenchs Forest,
New South Wales 2086 (AU). **WATERMANN, Anton**

[Continued on next page]

(54) Title: IMPROVED PUMP IMPELLER



(57) Abstract: An impeller for use in a centrifugal pump, the impeller (20) including a shroud having opposed faces, an outer peripheral edge portion and a rotation axis, a plurality of pumping vanes on one of the faces of the shroud and extending away from the rotation axis each pumping vane having an outer peripheral edge portion, and a plurality of auxiliary vanes (26) on the other face of the shroud, the auxiliary vanes of each having an outer edge portion wherein the dimension Da from the rotation axis to the outer peripheral edge portion of the shroud is greater than the dimension Db from the rotation axis to the outer edge portion of the auxiliary vanes.

WO 2004/111463 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.